
www.AccurateBuilding.com Copyright © 2004-2005 Date Published: 1974, 1976



Permissions For Reprints Contact: 1-800-640-8285

Lubrication & Maintenance Chart for Home Repairs

Basic Home Maintar	nence Lubrication C	hart		
UNIT	LUBRICANT	WHERE TO LUBRICATE	QUANTITY	WHEN
Doors, sliding closet	Silicone	Channels and wheels	1 to 2 drops and spread evenly	Twice yearly
Doors, sliding and overhead garage	Graphite oil	At locks, pulleys, along tracks	1 to 3 drops and work movable parts	Twice yearly
Doors, sliding shower and medicine cabinet	All-purpose white lubricant	Channels	1 to 2 drops and spread evenly	Twice yearly
Doors: storm door check	All-purpose white lubricant and lightweight household oil	On check's sliding surface, and/or rod	2 drops in check and 1 drop white grease on sliding surface	Twice yearly
Drawers, furniture doors	Sllicone, soap, or paraffin	Sliding surface	Light coat and spread	Twice yearly
Furnace blower motors	Heavy house- hold oil	In cups (some have none and don't need lube job)	2 to 3 drops	Twice per heatng season
Hinges	Lightweight household oil	Hinge pin	1 to 2 drops: remove pin, lubricate, and replace	Twice yearly
Locks	Graphite oil	Apply through keyhole	2 drops:Insert key and work back and forth	Twice yearly
Mowers, power	Heavy house- hold oil	As suggested by manufacturer	1 to 3 drops	Twice yearly
Machinery, heavy	Heavy house- hold oil	As suggested by manufacturer	As suggested by manufacturer	Twice yearly
Machinery, light	Lightweight household oil	As suggested by manufacturer	1 to 3 drops	Twice yearly
Plumbing fixtures	Graphite oil	Moving surface	1 to 2 drops	Twice yearly
Tools, Hand Tool	Lightweight household oil or all-purpose white lubricant	Where metal hits metal	1 to 2 drops and work in	Twice yearly
Tools, Outdoor Tool	Graphite oil	Exposed metal	Thin coat	After use
Tools, Power Tool	Lightweight household oil	As suggested by manufacturer	1 to 3 drops	Twice yearly
Window, casement and jalousie channels	All-purpose white lubricant	Channels	Thin coat, work in by moving window	Twice yearly
Window, casement and jalousie crank- ing mechanism	Lightweight household oil	Hand crank	1 to 2 drops	Twice yearly
Windows, double- hung	Silicone, soap, or paraffin	Channels	Thin coat, work in by moving window	Twice yearly
Window, latches	Lightweight household oil or all-purpose white lubricant	At joint	1 to 2 drops	Twice yearly

256